

Appl. No.: 09/673,598
Filed: October 18, 2000
Page 3

Amendments to the Claims:

Please amend Claims 1, 3, 7 and 13 and add new Claims 16-19 as follows:

C1
Cesth

1. (Currently Amended) A method of operating a solid state image sensor for the acquisition of an image presented to the sensor in response to an asynchronous stimulus, wherein said image sensor is operated in conjunction with at least one detector which, directly or indirectly, detects the said asynchronous stimulus, said image sensor is regularly reset so as to commence integration from a reset state of the sensor each time a predetermined period has elapsed, and an output from said at least one detector prior to ~~each reset~~ the end of a current predetermined period determines whether the subsequent reset operation of said image sensor ~~that reset~~ is inhibited or not in that if said output indicates ~~represents~~ the occurrence ~~detection~~ of said asynchronous stimulus then the subsequent reset operation of said image sensor ~~said reset~~ is inhibited.

2. (Previously Presented) A method according to claim 1 wherein the detector outputs a detection signal when said asynchronous stimulus is detected, and said detection signal is used to trigger a reset inhibition control signal for inhibiting a subsequent reset signal to the sensor.

3. (Currently Amended) A method of using a solid state image sensor comprising an array of sensing cells, for the acquisition of an image presented to the sensor in response to an asynchronous stimulus, wherein said image sensor is regularly reset so as to commence integrating from a reset state of the sensor each time a predetermined period has elapsed, and wherein a portion of the array of the sensor is read prior to the end of a current predetermined period ~~each said reset~~ and the value of this read is used to determine whether a subsequent reset signal to the sensor should be inhibited or not in that if said value indicates the occurrence of an asynchronous stimulus then said subsequent reset signal is inhibited.

Appl. No.: 09/673,598
Filed: October 18, 2000
Page 4

4. (Previously Presented) A method according to claim 3, wherein said portion of the array read prior to each reset comprises a plurality of sensing cells which are spatially distributed throughout the array of sensing cells.

5. (Previously Presented) A method according to claim 1 wherein the asynchronous stimulus is the opening of a camera shutter.

6. (Previously Presented) A method according to claim 1 wherein the asynchronous stimulus is a flash of light from a lighting strobe.

7. (Currently Amended) Image capture control apparatus suitable for use with a solid state image sensor for the acquisition of an image presented to the sensor in response to an asynchronous stimulus, wherein said image sensor is regularly reset so as to commence integration from a reset state of the sensor each time a predetermined period has elapsed, said apparatus comprising at least one detector means formed and arranged for detecting, in use of the apparatus, directly or indirectly, a said asynchronous stimulus, and reset inhibition control signal output means formed and arranged for generating a reset inhibition control signal in response to detection of said asynchronous stimulus and supplying it, directly or indirectly, in use of the apparatus, to a reset signal generating means operatively coupled to said solid state image sensor, so as to inhibit the application of at least one subsequent reset signal to the sensor whenever the occurrence of said asynchronous stimulus has been detected during a current predetermined period.

8. (Previously Presented) Image capture control apparatus according to claim 7 wherein said at least one detector means and said reset inhibition control signal output means are provided in a single device.

9. (Previously Presented) Image capture control apparatus according to claim 7, wherein said reset inhibition control signal output means and said reset signal generating means are provided together in a single device.

Appl. No.: 09/673,598
Filed: October 18, 2000
Page 5

10. (Previously Presented) Image capture control apparatus according to claim 7 wherein the detector is formed and arranged for detecting the opening of a camera shutter.

C1
11. (Previously Presented) Image capture control apparatus according to claim 7 wherein the detector is formed and arranged for detecting a flash of light from a lighting strobe.

12. (Previously Presented) A camera having a solid state image sensor, wherein is provided image capture control apparatus according to claim 7.

13. (Currently Amended) Image capture control apparatus suitable for use with a solid state image sensor for the acquisition of an image presented to the sensor in response to an asynchronous stimulus, said apparatus comprising at least one detector means formed and arranged for detecting, in use of the apparatus, directly or indirectly, a said asynchronous stimulus, and reset signal generating means operatively coupled to said solid state image sensor for regularly resetting the image sensor, in use of the apparatus, so that the sensor commences integrating from a reset state thereof each time a predetermined period has elapsed, reset inhibition control signal output means formed and arranged for generating a reset inhibition control signal in response to detection of said asynchronous stimulus and supplying it, directly or indirectly, in use of the apparatus to said reset signal generating means, so as to inhibit the application of at least one subsequent reset signal to the sensor.

14. (Previously Presented) A method according to Claim 3, wherein the asynchronous stimulus is the opening of a camera shutter.

15. (Previously Presented) A method according to Claim 3, wherein the asynchronous stimulus is a flash of light from a lighting strobe.

16. (Newly added) A method according to Claim 1, wherein said image sensor is performing integration during the predetermined period.

17. (Newly added) A method according to Claim 3, wherein said image sensor is performing integration during the predetermined period.

Appl. No.: 09/673,598
Filed: October 18, 2000
Page 6

18. (Newly added) Image capture control apparatus according to Claim 7, wherein said image sensor is performing integration during the predetermined period.

19. (Newly added) Image capture control apparatus according to Claim 13, wherein said image sensor is performing integration during the predetermined period.